

## Specifications

Nominal Voltage	6V	
Nominal Capacity (20HR)	1AH	
Dimension	Length	51mm (2.00 inches)
	Width	42mm (1.65 inches)
	Height	51mm (2.00 inches)
	Total Height (with Terminal)	56mm (2.20 inches)
	Approximate Weight	0.27 kg (0.60 lbs)
Battery Type	Valve Regulated Lead-Acid Battery, AGM Design	
Terminal Type	T1	
Rated Capacity	1.00AH	(20hr, 1.75V/cell, 25°C/77°F)
	0.96AH	(10hr, 1.75V/cell, 25°C/77°F)
	0.85AH	(5hr, 1.75V/cell, 25°C/77°F)
	0.85AH	(3hr, 1.60V/cell, 25°C/77°F)
	0.63AH	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	15A	
Internal Resistance	75mΩ	
Operating Temp. Range	Discharge:	-20°C (-4°F)~50°C (122°F)
	Charge:	-20°C (-4°F)~50°C (122°F)
	Storage:	-20°C (-4°F)~40°C (104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Container Material	ABS (Option: 94-HB & 94-V0 flame retardant case)	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86 %
Self Discharge	The CB Range of batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is recommended. For higher temperatures the time interval will be shorter.	



## Applications

- Uninterruptible Power Supply (UPS)
- Electric wheelchairs, scooters, bikes
- Electronic apparatus and equipment
- Alarm and security systems
- Emergency first responder equipment
- Emergency lighting
- Medical devices
- Electric carts
- Telecom equipment
- Switchgear
- Solar power systems



## Constant Current Discharge (Amperes Per Battery) at 25°C (77°F)

F.V. (V/cell) \ Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	3.86	2.62	1.94	1.15	0.628	0.365	0.282	0.185	0.121	0.101	0.052
1.65V	3.50	2.42	1.81	1.09	0.622	0.350	0.273	0.179	0.120	0.099	0.052
1.70V	3.17	2.24	1.71	1.03	0.608	0.345	0.262	0.174	0.118	0.097	0.051
1.75V	2.88	2.05	1.60	0.99	0.589	0.337	0.255	0.170	0.140	0.096	0.050
1.80V	2.56	1.87	1.46	0.96	0.563	0.325	0.250	0.166	0.117	0.093	0.050
1.85V	1.90	1.46	1.21	0.81	0.503	0.297	0.233	0.154	0.108	0.090	0.049


## Constant Power Discharge (Watts Per Cell) at 25°C (77°F)

F.V. (V/cell) \ Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	6.40	4.46	3.40	2.10	1.18	0.693	0.538	0.357	0.237	0.198	0.103
1.65V	5.94	4.20	3.23	2.00	1.18	0.667	0.524	0.347	0.235	0.196	0.103
1.70V	5.46	3.93	3.06	1.91	1.16	0.662	0.505	0.338	0.232	0.192	0.101
1.75V	5.10	3.69	2.91	1.85	1.13	0.647	0.492	0.331	0.229	0.188	0.100
1.80V	4.62	3.41	2.69	1.79	1.08	0.626	0.485	0.323	0.225	0.184	0.099
1.85V	3.48	2.70	2.26	1.54	0.97	0.578	0.454	0.303	0.213	0.179	0.098


## Dimensions

### T1 Terminal


Unit: mm (inches)




## Cycle Service Life




## Self Discharge Characteristics




## Discharge Characteristics




## Float Charging Characteristics



## Temperature Effects in Relation to Battery Capacity



## Temperature Effects on Long Term Float Life



## Contact Information

Canadian Batteries  
PO Box 154,  
Buckhorn, Ontario  
K0L 1J0 Canada

T: +1-888-730-8658  
F: +1-705-201-5466  
www.canadianbatteries.com